

ARCHITECT®

HIGH SECURITY READER ARC-G - RFID DESKTOP READER/ENCODER



COMPATIBILITY

- MIFARE Ultralight®
- Ultralight® C
- MIFARE® Classic
- Classic EV1
- MIFARE Plus®
- DESFire® EV2/ EV3
- NFC
- CPS3
- Moneo

LET YOUR IMAGINATION FLOW



PRINTING OF YOUR LOGO
using digital UV
or pad printing

Customization
of the multicolor LEDs
(RGB, 360 colors)

« Skin effect » new customization technology



STANDARDS



HIGH SECURITY DESKTOP APPLICATIONS

The Architect® ARC-G is a MIFARE Plus®/ DESFire® EV3 desktop reader/encoder. It is well suited for all your high security desktop and identification applications. By implementing the best STid security levels, this reader ensures confidentiality and integrity of all the communications.

HIGH SECURITY IDENTIFICATION

The ARC-G reader uses the latest MIFARE® contactless chip technologies with new data security mechanisms. It implements public encryption algorithms (TDES, AES, RSA, HMACSHA- 256...), as recommended and recognized by official IT security organization.

MULTI-TECHNOLOGY READER

The ARC-G readers/encoders are compliant with ISO14443 types A & B and ISO18092 standards. They support simultaneously the NXP MIFARE® chips: MIFARE Ultralight® & Ultralight® C, Classic & Classic EV1 (1kb, 4kb), MIFARE Plus® (S/X, 2kb/4kb), DESFire® EV1, EV2, EV3 - As well as special products like CPS3 cards (national healthcare professional ID card - IAS/ECC protocol), NFC, Moneo, iCLASS® and PicoPass® cards. With this multiple standard reading capacity, the reader is ready to answer easily cases of building extension, security evolution or migration.

CARD CONFIGURATION FEATURE (READ ONLY VERSION)

Secure read only ARC-G reader is completely user programmable with configuration cards. These cards, created with SECard software, are made to set up card reading security parameters (keys) and all the functional parameters (protocol, LEDs, buzzer, etc.).

DESIGN AND CUSTOMIZATION

STid offers a range of customization options to tailor your reader to your corporate image and integrate it fully in its installation environment.

SPECIFICATIONS

Operating frequency/Standards	13.56 MHz. ISO14443 types A & B, ISO18092 (NFC)
Chip compatibility	MIFARE Ultralight®, MIFARE Ultralight® C, MIFARE® Classic & Classic EV1, MIFARE Plus®, MIFARE® DESFire®, MIFARE® DESFire® EV1, EV2, EV3, NFC, SMART MX, CPS3, Moneo, iCLASS®, PicoPass®
Functions	Read only: private ID (sector/file) or Secure Protocol (Secure Plus) Read-Write (SSCP)
Reading distances*	Up to 8 cm (3.14") with a MIFARE® Classic card Up to 6 cm (2.36") with a MIFARE Plus®/DESFire® EV3 card
Communication interfaces	USB (optional ciphered - S35) Unidirectional or bidirectional (SSCP)
Light indicator	2 LEDs RGB - 360 colors Configuration by card, UHF technology, software and external command (0V) in R35/S35 By software in W35
Audio indicator	Internal buzzer Configuration by card, UHF technology, software and external command (0V) in R35/S35 By software in W35 2-pin plug-in connector (5 mm / 1.96"): O/C contact - Tamper detection signal
Material	ABS-PC UL-V0 (black) / ASA-PC-UL-V0 UV (white)
Dimensions (h x w x d)	107 x 80 x 26 mm / 4.21" x 3.14" x 1.01"
Operating temperatures	- 20°C to + 70°C (-4°F to 158°F) / Humidity: 0 - 95%
Protection / Resistance	Waterproof excluding connectors/Reinforced vandal proof structure IK10
Certifications	CE-FCC and UE
Part number	Secure read only - USB.....ARC-R35-G/PH5-5AB/y Secure read only / Secure Plus- USB.....ARC-S35-G/PH5-5AB/y Secure read/write - USB.....ARC-W35-G/PH5-5AA/y
y : casing color (1 : Black - 2 : White)	

DISCOVER OUR COMPATIBLE PRODUCTS



ISO Cards
MIFARE® hybrids cards



BSI / BMS
Wristbands



NFC
Smartphone



SECARD
Fully compatible with the SECARD
configuration
kit and the SSCP protocol



SWEDGE
Enrollment kit to import cards
numbers directly to any
applications (keyboard/wedge)

*Caution: information about the distance of communication: mea sured from the center of the antenna, depending on the type of identifier, size of the identifier, operating environment of the reader, power supply voltage and reading functions (secure reading).

Legal statements: STid, STid Mobile ID® and Architect® are trademarks of STid SAS. All other trademarks are property of their respective owners. This document is the exclusive property of STid. STid reserves the right to stop any product or service for any reason and without any liability - Noncontractual photographs.

Headquarters / EMEA

13850 Gréasque, France
Tel.: +33 (0)4 42 12 60 60

PARIS-IDF Office

92290 Châtenay-Malabry, France
Tel.: +33 (0)1 43 50 11 43

STid UK Ltd. LONDON

Hayes UB11 1FW, UK
Tel.: +44 (0) 192 621 7884

STid UK Ltd.

Gallows Hill, Warwick CV34 6UW, UK
Tel.: +44 (0) 192 621 7884

NORTH AMERICA Office

New York, NY 10005, USA
Tel.: +1 310 803 2114

LATINO AMERICA Office

Cuahtémoc 06600 CDMX, México
Tel.: +521 (55) 5256 4706

AUSTRALIA / APAC Office

Ultimo, Sydney NSW 2007, Australia
Tel.: +61 (0)2 9274 8853

info@stid.com

www.stid-security.com