

# MULTI-TECHNOLOGY KEYPAD READER

125 kHz, MIFARE® DESFIRE® EV2 & EV3, NFC BLUETOOTH®



Available in touchscreen and standard versions



## BENEFITS

- Compatible with legacy Prox 125 kHz technologies
- Seamless migration to secure and mobile technologies
- Multi-factor identification with capacitive keypad
- Modular concept for maximum cost optimization



125 kHz  
13.56 MHz



BLUETOOTH®



TTL  
RS 485



EAL5+



Water  
resistant  
EQ IP65



Vandal-proof  
IK08



4-COLOR  
LOGO

- Print your logo
- Casing color
- Skin effect customization

The Architect® Blue Hybrid reader facilitates your migrations to secure and mobile technologies. It combines three identification technologies 125 kHz, 13.56 MHz and Bluetooth® with a capacitive vandal-proof keypad.

## MULTI-TECHNOLOGY READER

Offering support for the widest range of contactless identification technologies, the reader is the ideal choice for making a gradual transition to high security. It simplifies management of upgrades, technological migrations and complex multi-site configurations.

### 125 kHz Prox technologies

The reader is compatible with many legacy Prox technologies: EM®, NEDAP®, CROSSPOINT®, Wiegand 26, 34, 35 and 37 bits formats...

### RFID MIFARE® DESFire® EV2 & EV3

It supports the latest contactless technologies with new data security features:

- **Secure Messaging EV2:** protection against attacks via interleaving and replay.
- **Proximity Check:** protection against relay attacks.

The reader supports the use of public security algorithms recognized by specialized and independent organizations in information security (ANSSI French cybersecurity agency and FIPS). It includes an EAL5+ crypto processor to improve data protection and confidentiality.

### Bluetooth® and NFC smartphones

The smartphone becomes your access key and removes all the limitations of traditional access control cards.

STid offers 6 modes of Prox, long distance or handsfree identification to make your access control both secure and instinctive!

## VANDAL-PROOF CAPACITIVE KEYPAD

Equipped with a backlit keypad, the reader allows multi-factor identification of users by combining the reading of an RFID or virtual card with the input of a personal keypad code.

Thanks to its different operating modes, the keypad can be used for identification or to activate additional functions (alarm...).

The same reader can also operate in multiple mode e.g. it authorizes card reading for personnel or just code entry for visitors or temporary workers.

## A CUSTOMIZED SCALABLE CONFIGURATION

The Architect® Blue reader can be customized to meet your needs: all the features and security levels of the readers in your organization can be upgraded - by RFID credential, virtual card or protocol.

The scalability allows you to remove the 125 kHz module once your technology migration is completed and / or to implement new functionality such as a touchscreen.

## OPEN TECHNOLOGIES FOR EASY INTEGRATION

The reader is compatible with many access control systems and accepts multiple interfaces and protocols (Wiegand, Clock&Data, SSCP® v1 & v2 and OSDP™ v1 & v2).

## STANDING THE TEST OF TIME

The design of the reader makes it very robust in harsh environments. It can therefore be used outdoors and offers high levels of resistance to vandalism (IK08 certified).

## SPECIFICATIONS

Operating frequency / Standards	125 kHz 13.56 MHz: ISO14443 types A & B, ISO18092 Bluetooth®																				
Chip compatibility	EM42xx / EM4x50 / Wiegand 26, 34, 35 and 37 bits / Nedap® / Crosspoint® format MIFARE® Ultralight® & Ultralight® C, MIFARE® Classic & Classic EV1, MIFARE Plus® (S/X) & Plus® EV1, MIFARE® DESFire® 256, EV1, EV2 & EV3, PicoPass® (CSN only), iCLASS™ (CSN only*) STid Mobile ID® (NFC HCE and Bluetooth® virtual card), Orange Pack ID																				
Functions	CSN, pre-configured (Easyline - PC2) and secure read-only / Controlled by protocol (read/write)																				
Communication interfaces & protocols	TTL Wiegand or Clock&Data (ISO2) output (encrypted communication option - SX1) / RS485 output (encrypted communication option - SX3) with secure SSCP® v1 and v2 communication protocols, OSDP™ v1 (plain communication) and v2 (SCP secure communication) / Compatible with EasySecure interface																				
Keypad	Sensitive / Capacitive keypad - 12 backlit keys - Functions: Card AND Key / Card OR Key Configuration by standard or virtual card with STid Settings application, software or external command (0V) according to the interface																				
Reading distances**	Up to 6 cm / 2.36" with a 125 kHz card Up to 6 cm / 2.36" with a MIFARE® DESFire® EV2 card Up to 20 m / 65.6 ft with a Bluetooth® smartphone (adjustable distances on each reader)																				
Data protection	Yes - EAL5+ secure data storage with certified crypto processor																				
Light indicators	2 RGB LEDs - 360 colors ▲ ▲ ▲ Configuration by standard or virtual card with STid Settings application, software or external command (0V) according to the interface																				
Audio indicator	Internal buzzer with adjustable intensity Configuration by standard or virtual card with STid Settings application, software or external command (0V) according to the interface																				
Relay	Automatic tamper direction management SSCP® / OSDP™ command according to the interface																				
Power requirement	210 mA / 12 VDC Max																				
Power supply	7 VDC to 28 VDC																				
Connections	10-pin plug-in connector (5 mm / 0.2") - 2-pin plug-in connector (5 mm / 0.2"): O/C contact - Tamper detection signal																				
Material	ABS-PC UL-V0 (black)																				
Dimensions (h x w x d)	145.6 x 80 x 25.7 mm / 5.7" x 3.15" x 0.98" (general tolerance following ISO NFT 58-000 standard)																				
Operating temperatures	- 30°C to + 70°C / - 22°F to + 158°F																				
Tamper switch	Accelerometer-based tamper detection system with key deletion option (patented)																				
Protection / Resistance	IP65 Level - Weather-resistant with waterproof electronics (CEI NF EN 61086 homologation) Humidity: 0 - 95% / Reinforced IK08 certified vandal-proof structure																				
Mounting	Compatible with any surfaces and metal walls - Wall mount/Flush mount: - European 60 & 62 mm / 2.36" & 2.44" - American (metal/plastic) - 83.3 mm / 3.27" - Dimensions: 101.6 x 53.8 x 57.15 mm / 3.98" x 2.09" x 2.24" - Examples: Hubbel-Raco 674, Carlon B120A-UP																				
Certifications	CE (Europe), FCC (USA), IC (Canada) and UL																				
Part numbers	<table border="0"> <tr> <td>Easyline pre-configured - Wiegand protocol .....</td> <td>ARCS-RX1-J/PC2-3x/1</td> </tr> <tr> <td>Secure read only - TTL .....</td> <td>ARCS-RX1-J/BT2-xx/1</td> </tr> <tr> <td>Secure read only / Secure Plus - TTL .....</td> <td>ARCS-SX1-J/BT2-xx/1</td> </tr> <tr> <td>Secure read only - RS485 .....</td> <td>ARCS-RX3-J/BT2-7AB/1</td> </tr> <tr> <td>Secure read only / Secure Plus - RS485 .....</td> <td>ARCS-SX3-J/BT2-7AB/1</td> </tr> <tr> <td>Secure read only / EasySecure Interface - RS485 .....</td> <td>ARCS-RX3-J/BT2-7AA/1</td> </tr> <tr> <td>Secure read only / Secure Plus / EasySecure Interface - RS485 .....</td> <td>ARCS-SX3-J/BT2-7AA/1</td> </tr> <tr> <td>Controlled by SSCP® v1 protocol - RS485 .....</td> <td>ARCS-WX3-J/BT2-7AA/1</td> </tr> <tr> <td>Controlled by SSCP® v2 protocol - RS485 .....</td> <td>ARCS-WX3-J/BT2-7AD/1</td> </tr> <tr> <td>Controlled by OSDP™ v1 &amp; v2 protocol - RS485 .....</td> <td>ARCS-WX3-J/BT2-7OS/1</td> </tr> </table>	Easyline pre-configured - Wiegand protocol .....	ARCS-RX1-J/PC2-3x/1	Secure read only - TTL .....	ARCS-RX1-J/BT2-xx/1	Secure read only / Secure Plus - TTL .....	ARCS-SX1-J/BT2-xx/1	Secure read only - RS485 .....	ARCS-RX3-J/BT2-7AB/1	Secure read only / Secure Plus - RS485 .....	ARCS-SX3-J/BT2-7AB/1	Secure read only / EasySecure Interface - RS485 .....	ARCS-RX3-J/BT2-7AA/1	Secure read only / Secure Plus / EasySecure Interface - RS485 .....	ARCS-SX3-J/BT2-7AA/1	Controlled by SSCP® v1 protocol - RS485 .....	ARCS-WX3-J/BT2-7AA/1	Controlled by SSCP® v2 protocol - RS485 .....	ARCS-WX3-J/BT2-7AD/1	Controlled by OSDP™ v1 & v2 protocol - RS485 .....	ARCS-WX3-J/BT2-7OS/1
Easyline pre-configured - Wiegand protocol .....	ARCS-RX1-J/PC2-3x/1																				
Secure read only - TTL .....	ARCS-RX1-J/BT2-xx/1																				
Secure read only / Secure Plus - TTL .....	ARCS-SX1-J/BT2-xx/1																				
Secure read only - RS485 .....	ARCS-RX3-J/BT2-7AB/1																				
Secure read only / Secure Plus - RS485 .....	ARCS-SX3-J/BT2-7AB/1																				
Secure read only / EasySecure Interface - RS485 .....	ARCS-RX3-J/BT2-7AA/1																				
Secure read only / Secure Plus / EasySecure Interface - RS485 .....	ARCS-SX3-J/BT2-7AA/1																				
Controlled by SSCP® v1 protocol - RS485 .....	ARCS-WX3-J/BT2-7AA/1																				
Controlled by SSCP® v2 protocol - RS485 .....	ARCS-WX3-J/BT2-7AD/1																				
Controlled by OSDP™ v1 & v2 protocol - RS485 .....	ARCS-WX3-J/BT2-7OS/1																				

## DISCOVER OUR CREDENTIALS AND MANAGEMENT TOOLS



ISO cards & key holders  
(125 kHz, 13.56 MHz...)



Bluetooth® & NFC smartphones /  
smartwatches using  
STid Mobile ID® application



### SECARD

SECard configuration kit  
and SSCP® v1 & v2  
& OSDP™ protocols

Detection zone  
13.56 MHz + NFC  
+ Bluetooth®

Detection zone  
125 kHz



\*Our readers only read the iCLASS™ chip serial number / UID PICO1444-3B. They do not read iCLASS™ cryptographic protection or the HID Global serial number / UID PICO 15693.

\*\*Caution: information about the distance of communication: measured from the center of the antenna, depending on the type of identifier, size of the identifier, operating environment of the reader, power supply voltage and reading functions (secure reading).

Legal statements: STid, STid Mobile ID®, SSCP® and Architect® are trademarks of STid SAS. All other trademarks are property of their respective owners. This document is the exclusive property of STid. STid reserves the right to stop any product or service for any reason and without any liability - Noncontractual photographs.

### Headquarters / EMEA

13850 Créasque, France  
Tel.: +33 (0)4 42 12 60 60

### PARIS-IDF

92290 Châtenay-Malabry, France  
Tel.: +33 (0)1 43 50 11 43

### STid UK Ltd.

Gallows Hill, Warwick CV34 6UW, UK  
Tel.: +44 (0) 192 621 7884

### NORTH AMERICA

Irving, Texas 75063-2670, USA  
Tel.: +1 469 524 3442

### LATINO AMERICA

San Rafael 06470 CDMX, México  
Tel.: +52 (55) 5256 4706

info@stid.com

www.stid-security.com